

KIV 105°C WIRE

KIV 105°C 細芯電線



TUNG-YANG

◆說明：

- ◎導體：裸軟 銅線絞合
- ◎絕緣：PVC
- ◎耐溫：105°C
- ◎耐電壓：600V

◆應用：

- ◎ 一般儀器、機械及變電設備，控制或傳遞訊息之系統。

Construction:

◆構造：



Conductor 導體		Insulation Diameter	Insulation Thickness	Overall Diameter	Characteristics		Item Number
截面積	線數/線徑	蕊線外徑	絕緣厚度	完成外徑	導體電阻	試驗電壓	產品編號
MM ²	No./mm	mm	mm	mm	20°C (Ω/KM)	V/MIN	AG 系列
0.5	20/0.18 BC	0.9	0.6	2.1	36.70	1000	AG0.5S01CA
0.75	30/0.18 BC	1.1	0.8	2.8	24.40	1500	AG0.75S01CA
1.25	50/0.18 BC	1.5	0.8	3.1	14.70	1500	AG1.25S01CA
2	37/0.26 BC	1.8	0.8	3.4	9.88	1500	AG2.0S01CA
3.5	65/0.26 BC	2.3	0.8	4.1	5.32	1500	AG3.5S01CA
5.5	104/0.26 BC	3.0	1.0	5.1	3.34	1500	AG5.5S01CA
8	150/0.26 BC	3.8	1.2	6.2	2.40	1500	AG8.0S01CA
14	7/37/0.26 BC	5.0	1.4	7.8	1.39	2000	AG14S01CA
22	7/60/0.26 BC	6.4	1.8	10.0	0.848	2000	AG22S01CA
30	19/30/0.26 BC	7.6	1.8	11.2	0.635	2000	AG30S01CA
38	7/16/0.26 BC	8.3	1.8	11.9	0.515	2500	AG38S01CA
50	19/50/0.26 BC	9.8	2.1	14.0	0.381	2500	AG50S01CA
60	19/60/0.26 BC	10.8	2.3	15.4	0.318	2500	AG60S01CA
80	37/41/0.26 BC	12.5	2.3	17.1	0.239	2500	AG80S01CA
100	37/51/0.26 BC	13.9	2.3	18.2	0.192	2500	AG100S01CA
125	37/64/0.26 BC	15.2	2.4	20.0	0.155	3000	AG125S01CA
150	37/76/0.26 BC	16.6	2.6	22.0	0.130	3000	AG150S01CA
200	37/102/0.26 BC	19.2	3.0	25.5	0.0979	3000	AG200S01CA
250	37/127/0.26 BC	21.5	3.0	27.5	0.0775	3000	AG250S01CA
325	35/7/25/0.26 BC	24.9	3.5	32.0	0.0601	3000	AG325S01CA

B.C：裸銅線

AG-01